



# Sandell Manufacturing Company, Inc.

www.sandellmfg.com

e-mail: moreinfo@sandellmfg.com

## CORPORATE OFFICE

310 Wayto Rd. • Schenectady, NY 12303

Phone: (518) 357-9757

1 (800) 283-3888 • Fax: (518) 357-9636

## BRANCH OFFICE

1700 Vanderbilt Rd. • Birmingham, AL 35234

Phone: (205) 263-1030

1 (877) SANDELL • Fax: (205) 263-1033

# Sandell Copper Fabric Flashing

## MATERIAL SAFETY DATA SHEET

### SECTION 1 MATERIAL IDENTIFICATION INFORMATION

Mineral Spirits

Copper (Insert Solid)

Cotton Fabric (Insert Solid)

Granite Grit (Insert Solid)

ACGH TLV 500PPM

*Note:* None of the information listed on this MSDS should apply to application or use in the finished state. Only under the most adverse conditions during the manufacturing state is this data applicable.

### SECTION 2 PHYSICAL/CHEMICAL CHARACTERISTICS

**Boiling Point:** 315°F (157°C)

**Specific Gravity (H<sub>2</sub>O=1):** 1.1

**Vapor Pressure:** 68°F (20°C)

**Melting Point:** N/A

**Vapor Density:** 3.9

**Evaporation Rate:** 0.1

**Solubility in Water:** None

**Appearance and Odor:** Brown to black solid with faint petroleum odor.

### SECTION 3 FIRE AND EXPLOSION HAZARD DATA

**Flash Point:** Over 400°F (204°C)

**Flammability Limits in Air Volume:** 1.0–7.0

**Extinguisher Media:** Foam, CO<sub>2</sub>, or Dry Chemical

**Special Fire Fighting Procedures:** Do not use water.

### SECTION 4 REACTIVITY HAZARD DATA

**Stability:** Stable

**Conditions to Avoid:** None (Non-Reactive)

**Hazardous Polymerization:** Conditions to avoid—poor ventilation can cause excessive inhalation of solvent vapors.

### SECTION 5 HEALTH HAZARD DATA

**Sign and Symptoms of Exposure:** Inhalation of solvent in poorly ventilated area may cause dizziness.

**Medical Conditions Generally Aggravated by Exposure:** Excessive skin contact can lead to dry irritated skin.

**Emergency First Aid Procedures:** Seek medical assistance for further treatment, observation and support if necessary.

### SECTION 6 CONTROL AND PROTECTIVE MEASURES

**Respiratory Protection:** Area should be well-ventilated.

**Protective Gloves:** Normal work gloves

**Eye Protection:** Safety glasses or goggles

**Ventilation to be Used:** Local exhaust

**Other Protective Clothing and Equipment:** None

### SECTION 7 PRECAUTIONS FOR SAFE HANDLING AND USE/LEAK PROCEDURE

**Steps to be Taken if Material is Spilled or Released:** Area should be well-ventilated, respirators can be used.

**Precautions to be Taken in Handling and Storage:** Do not store above 120°F (49°C).

**Other Precautions and/or Special Hazards:** None