



Sandell Manufacturing Company, Inc.

www.sandellmfg.com

e-mail: moreinfo@sandellmfg.com

CORPORATE OFFICE

310 Wayto Rd. • Schenectady, NY 12303
Phone: (518) 357-9757
1 (800) 283-3888 • Fax: (518) 357-9636

BRANCH OFFICE

1700 Vanderbilt Rd. • Birmingham, AL 35234
Phone: (205) 263-1030
1 (877) SANDELL • Fax: (205) 263-1033

Sandell Copper Kraft Duplex Flashing

MATERIAL SAFETY DATA SHEET

SECTION 1 MATERIAL IDENTIFICATION INFORMATION

Mineral Spirits (ACGIH TLV 500 PPM)
Copper (Insert Solid)
Cotton Fabric (Insert Solid)
Granite Grit (Insert Solid)
Reinforced Kraft Paper
Asphalt (Insert Solid)

Note: No toxic chemical subject to the reporting of section 313 of the Title III and of 40 CFR 372 are present.

None of the information listed on this MSDS should apply to application or use in the finished state. Only under the most adverse conditions during the manufacturing state is this data applicable.

SECTION 2 PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: 315°F to 900°F (157°C to 482°C)

Specific Gravity (H₂O = 1): 1.1

Vapor Pressure: 68°F (20°C)

Melting Point: N/A

Vapor Density: 3.9

Evaporation Rate: 0.1

Solubility in Water: N/A

Appearance and Odor: Brown to black solid with faint petroleum odor.

SECTION 3 FIRE EXPLOSION HAZARD DATA

Flash Point and Method Used: Over 400°F (204°C)

Extinguisher Media: Foam, CO₂ or Dry Chemical

Special Fire Fighting Procedures: Do Not Use Water.

SECTION 4 REACTIVITY HAZARD DATA

Stability: Stable

Conditions to Avoid: Poor ventilation can cause excessive inhalation of solvent vapors.

SECTION 5 HEALTH HAZARD DATA

Signs and Symptoms: Inhalation of solvent in poorly ventilated area may cause dizziness.

Medical Conditions Generally Aggravated by Exposure: Excessive skin contact can lead to dry irritated skin.

SECTION 6 CONTROL AND PROTECTIVE MEASURES

Respiratory Protection: None under normal conditions.

Ventilation: Local exhaust if material is heated.

Protective Gloves: If material is heated.

Other Protective Clothing or Equipment: N/A

Mechanical: N/A

Eye Protection: Safety glasses

SECTION 7 PRECAUTIONS FOR SAFE HANDLING AND USE/LEAK PROCEDURES

Steps to be Taken if Material is Released or Spilled: Sweep up or pick up to avoid slipping hazard.

Protective Gloves: If material is heated.

Waste Disposal Method: Dispose of in landfill in compliance with applicable federal, local, and state regulations.

Precautions to be Taken in Handling and Storing: Store in cool, dry place.