



Sandell Manufacturing Company, Inc.

www.sandellmfg.com

e-mail: moreinfo@sandellmfg.com

CORPORATE OFFICE

310 Wayto Rd. • Schenectady, NY 12303
Phone: (518) 357-9757
1 (800) 283-3888 • Fax: (518) 357-9636

BRANCH OFFICE

1700 Vanderbilt Rd. • Birmingham, AL 35234
Phone: (205) 263-1030
1 (877) SANDELL • Fax: (205) 263-1033

Sandell Sando-Seal Flashing

MATERIAL SAFETY DATA SHEET

SECTION 1 MATERIAL IDENTIFICATION INFORMATION

Trade Names and Synonyms: Rubberized asphalt membrane with polyolefin film or fabric.

This sheet is applicable to: CCW-701, all configurations, CCW-705, CCW-705R, CCW-707, CCW-711, all configurations, CCW-711N.

Chemical Family: Mixture

Product Use: Waterproofing

Hazardous Ingredients: Asphalt, Aromatic Oil, and Solvent Extract

SECTION 2 PHYSICAL/CHEMICAL CHARACTERISTICS

Physical State: Solid

Vapor Density: N/A

Specific Gravity: 1.05

Boiling Point: N/A

Coef. Water/Oil Dist.: N/A

Freezing Point: N/A

Volatiles BvW t(%): N/A

pH: N/A

Corrosivity: N/A

Evaporation Rate: N/A

Solubility in Water: Insoluble

Appearance and Odor: Black adhesive sheet with slight petroleum odor.

SECTION 3 FIRE AND EXPLOSION HAZARD DATA

Flammability: Yes

Upper Flammable Limit: (% by Vol.)

Sensitivity to Impact: None

Extinguishing Media: CO₂, Foam, Dry Chemical

Special Fire Fighting Procedures: Wear NIOSH/MSHA approved respirators, or self-contained breathing apparatus.

Unusual Fire and Explosion Hazards: None

SECTION 4 REACTIVITY HAZARD DATA

Chemical Stability: Stable

Conditions to Avoid: Avoid contact with strong oxidizing materials or basic compounds.

Incompatibility (Materials to Avoid): Strong Oxidizers.

Hazardous Decomposition Products: Thermal decomposition products include CO and CO₂.

Hazardous Polymerization: Will not occur

SECTION 5 TOXICOLOGICAL PROPERTIES

Route of Entry: Skin contact, skin absorption, eye contact, inhalation, ingestion.

Effects of Acute Exposure to Product: May cause eye irritation if oil residue on hands is wiped or rubbed into the eyes.

Effects of Chronic Exposure: Repeated or prolonged contact with oil in this product may cause skin irritation.

Irritancy of Product: May irritate skin, eyes, and respiratory tract.

SECTION 6 PREVENTIVE MEASURES

Personal Protective Equipment:

Gloves: Rubber gloves and/or the use of barrier creams to minimize skin exposure are recommended.

Respirator: Provide adequate ventilation in confined areas or respirators if material is heated.

Other: Source of clean water should be available in the work area for flushing eyes and skin.

Engineering Controls (EG. Ventilation Enclosed Process): Provide local exhaust or mechanical exhaust if required to maintain concentration of vapors below 100 ppm.

Leak or Spill Procedures: In the event material is released or spilled, peel off material and dispose of properly.

Waste Disposal: Dispose of according to local, state and federal regulations.

Handling Procedures and Equipment: Avoid contact with skin. Clean fingernails and wash hands with soap and water after handling. Avoid rubbing eyes while handling product. Do not take internally. Avoid removing release paper where spark may ignite flammable vapors.

FOR PROFESSIONAL USE ONLY, KEEP OUT OF REACH OF CHILDREN!

SECTION 7 FIRST AID MEASURES

Eye Contact: Immediately flush with plenty of water for at least 15 minutes. Call a physician.

Skin Contact: Wash promptly with soap and water. Remove all material under fingernails. See a physician if irritation develops.

Inhalation: No known adverse effects. Due to the physical nature of this product, inhalation is unlikely.

Ingestion: As this product is a solid, ingestion is unlikely. Should ingestion occur, contact a physician.