

**SANDELL'S REBAR POSITIONERS**


**Sandell's Single Rebar Positioners**

**WIRE:** (Carbon Steel)  
Cold-drawn ste wire conforming to ASTM A 82  
Tensile strength - 80,000 p.s.i.  
Yield Point - 70,000 p.s.i. Minimum


**WIRE DIAMETER:**  
9 Gauge

**FINISHES:**  
Mill Galvanized Conforms to ASTM A 641  
Hot-dip Galvanized Conforms to ASTM A 153

**SIZES:**  
6" for 8" Block (Single)  
10" for 12" Block (Single)



Single Rebar Positioner



Double Rebar Positioner

**Sandell's Double Rebar Positioners**

**WIRE:** (Carbon Steel)  
Cold-drawn ste wire conforming to ASTM A 82  
Tensile strength - 80,000 p.s.i.  
Yield Point - 70,000 p.s.i. Minimum

**WIRE DIAMETER:**  
9 Gauge

**FINISHES:**  
Mill Galvanized Conforms to ASTM A 641  
Hot-dip Galvanized Conforms to ASTM A 153

**SIZES:**  
6" for 8" Block (Double)  
10" for 12" Block (Double)

**TECHNICAL ASSISTANCE:**

Call Sandell directly for technical assistance or product questions:

New York: 800.283.3888  
Alabama: 877.726-3355  
Wisconsin: 800.323-3565



[www.sandellmfg.com](http://www.sandellmfg.com)

Amendments / Notes:


Sandell Employee:

Date: