

SANDELL'S S-600 PRIMER

DESCRIPTION

S-600 Primer is a water-based, high tack, primer, specially formulated to provide good initial adhesion and excellent permanent adhesion of Sandell Sando-Seal.

USES

S-600 Primer is used to precondition all structural concrete or masonry surfaces on which the Sando-Seal membrane is to be applied. S-600 Primer can be used in ambient and substrate temperatures above 25°F (-4°C). S-600 Primer is an integral component of Sandell's waterproofing membranes. Substitution is not allowed.

APPLICATION

- ❖ S-600 Primer may be applied by explosion proof sprayer, roller or brush. Vapors during spray are hazardous. Wear appropriate protection.
- ❖ Use a heavy nap roller with natural material such as wool to avoid deterioration.
- ❖ Apply primer to clean, dry, dust- and frost-free surfaces at a coverage of 250 to 300 square feet per gallon (6-7sq.m./ l). Spread primer evenly. Avoid deep puddles which will lengthen dry time.
- ❖ Allow S-600 Primer to dry at least one hour. On warm days drying may occur more rapidly.
- ❖ Priming should be limited to what can be covered with Sando-Seal in one working day. Any areas not covered with Sando-Seal during the day may require additional priming. Be sure to cover open primer pails when not in use.
- ❖ Clean tools with mineral spirits or paint thinner at the end of the day. Rollers can be wrapped tightly

overnight in aluminum foil. (Mineral spirits and paint thinner are combustible liquids and should be used with care.)

PROPERTY	MINIMUM VALUE
Weight per gallon	7.69 lbs
Solids Content	25% by weight
Tack-Free Time	25-30 Minutes at 75°F (4°C)
Flash Point	44°F (7°C)



TECHNICAL ASSISTANCE:

Call Sandell directly for technical assistance or product questions:

- New York: 800.283.3888
- Alabama: 877.726-3355
- Wisconsin: 800.323-3565

 www.sandellmfg.com

Revised: 01.25.2010

Amendments / Notes:

Sandell Employee:

Date:

CORPORATE OFFICE
NEW YORK
Toll Free: 800-283-3888
Fax: 518-357-9757

BRANCH OFFICE
ALABAMA
Toll Free: 877-SANDELL
Fax: 205-263-1033

BRANCH OFFICE
WISCONSIN
Toll Free: 800-323-3565
Fax: 414-764-6993