

SANDELL'S SANDO-DRY MASTIC

DESCRIPTION

Sando-Dry Mastic is a solvent-based, rubberized asphalt mastic. Sando-Dry Mastic has excellent adhesion to Sandell Advanced Composites, structural concrete, masonry, wood and stone. Sando-Dry Mastic is supplied in five gallon pails (19 L) and one quart (0.9 L) cartridges.

USES

Sando-Dry Mastic is designed to protect the terminations, patches and overlaps in detail areas. On vertical applications Sando-Dry Mastic must be applied to bottom terminations as well as top terminations. Sando-Dry Mastic is an integral component of the Sandell Advanced Composite Waterproofing System. Substitution is not allowed.

APPLICATION

Apply Sando-Dry Mastic either with a caulking gun or trowel. If applied with a caulking gun, strike the bead off the with a trowel to about a 1.8" (3 mm) thickness and a 1.2" to 1" (13.25 mm) width. On the bottom edge of vertical applications Sando-Dry Mastic should be troweled upward. Sando-Dry Mastic should be used liberally around protrusions, drains and other areas requiring patch pieces.

The amount of Sando-Dry Mastic will vary widely from job to job. One-gallon (4 L) of Sando-Dry Mastic applied in a bead 2" wide by 1.4" (50 mm x 6 mm) will extend 850 linear feet (259 m). Clean tools with mineral spirits or paint thinner at the end of each day. Mineral spirits

and paint thinner are combustible liquids and should be used in accordance with the safety instructions, detailed in the MSDS.

PROPERTY	MINIMUM VALUE
Weight per gallon	11 lbs.
VOC (Volatile Organic Content)	240 grams / liter (max)
Viscosity - Brookfield #6, 20 rpm	< 4,000 poise
Flash Point	> 100°F (>38°C)


TECHNICAL ASSISTANCE:

Call Sandell directly for technical assistance or product questions:

New York: 800.283.3888

Alabama: 877.726-3355

Wisconsin: 800.323-3565



www.sandellmfg.com

Amendments / Notes:

--	--

Sandell Employee:

Date:

CORPORATE OFFICE
 NEW YORK
Toll Free: 800-283-3888
Fax: 518-357-9757

BRANCH OFFICE
 ALABAMA
Toll Free: 877-SANDELL
Fax: 205-263-1033

BRANCH OFFICE
 WISCONSIN
Toll Free: 800-323-3565
Fax: 414-764-6993