

SANDELL'S TROWEL MASTIC

DESCRIPTION

A cut-back asphalt, containing long-fibered material, manufactured in proper consistency for easy application. It is manufactured to a trowel grade consistency which will provide durable, elastic coating highly resistant to weathering while providing excellent adhesion properties. Sandell Trowel Mastic performs well over a wide range of temperature and weather conditions. It complies with all requirements of Federal Specifications SS-C—153, Type 1 and ASTM 4586-88, Type 1 and SSPC No. 12.

USES

Copper Laminated Flashings

Splicing:

Sandell Asphalt Trowel Mastic is the preferred mastic to be used while splicing copper flashings. Material should be overlapped a minimum of 4" and coating of Sandell Asphalt Trowel Mastic applied to a yield of 25 sq. ft. per gallon coverage.

Vertical Masonry Surfaces:

Sandell Asphalt Trowel Mastic should be spotted to vertical surfaces to receive flashing. Sandell Asphalt Trowel Mastic will hold the flashing in place while masonry is set. Flashing should be secured in a reglet or masonry joint or mechanical fastener.

General Purpose:

Sandell Asphalt Trowel Mastic can also be used as a general purpose cement for repairing leaks in asphalt roofs, metal roofs, chimneys, flues, down spouts and concrete.

CONSISTENCY

Sandell Asphalt Trowel Mastic is a heavy, trowel grade which spreads easily and adheres to most surfaces. Coverage should yield approximately 25 sq. ft. per

gallon. Sandell Asphalt Trowel Mastic retains its elasticity and ductility, thus coating will resist extreme variations in temperature.

SURFACE PREPARATION

All surfaces should be clean, dry, and free from grease, oil, or other loose foreign matter.

PACKAGE SIZE

Available in 5 gallon pails.

PHYSICAL PROPERTIES

Boiling Point:	650°F (343°C)
Flash Point and Method:	110°F (43°C)
Solubility in Water:	None
Appearance:	Black Paste


TECHNICAL ASSISTANCE:

Call Sandell directly for technical assistance or product questions:

New York:	800.283.3888
Alabama:	877.726-3355
Wisconsin:	800.323-3565



www.sandellmfg.com

Amendments / Notes:

--	--

Sandell Employee: _____

Date: _____

CORPORATE OFFICE
NEW YORK
Toll Free: 800-283-3888
Fax: 518-357-9757

BRANCH OFFICE
ALABAMA
Toll Free: 877-SANDELL
Fax: 205-263-1033

BRANCH OFFICE
WISCONSIN
Toll Free: 800-323-3565
Fax: 414-764-6993